

EASY-CLEAN BULLET MAGNET



DESCRIPTION

The Greenwood Easy Clean Bullet Magnet is similar to the standard bullet magnet for extracting ferrous metal contamination from either gravity fed or pneumatic pipelines. However it benefits from the easy clean facility. It is normally fitted vertically or horizontally in pneumatic process lines or intake lines with high velocity for powders, and other free flowing ingredients.

As they need to be cleaned regularly to maintain efficiency, the easy clean facility makes this job much simpler and faster for the operatives, reducing downtime. It also improves operator health and safety by reducing the risk of cuts and abrasions which could possibly occur from removing sharp metal fragments from the powerful internal magnet.



FEATURES

- Easily installed
- Quick release stainless steel capped swing bolts
- Connections manufactured to your requirements
- Fast hazard free easy clean facility
- Ideal for free-flowing powders and granules: plastics, food ingredients
- Food quality seal
- Supplied with full documentation and material certificates

SPECIFICATION

- Powerful high intensity rare earth magnets
- Suitable for pressure up to 2 bar
- Magnet strength up to 8000 gauss
- Fully welded and crack and crevice free to food industry standards
- Bead blast or polished finish internally – externally
- Optional safety switch
- Magnet strength tested and certified
- Suitable for use in Atex zone 20 environment

Greenwood Magnetics Ltd
Unit 1 Buckley Road Industrial Estate
Buckley Road, Rochdale
Lancashire OL12 9EF

T +44 (0) 1706 645 824

F +44 (0) 1706 642 458

E sales@greenwoodmagnetics.com